

## LI-HNIP-01 Hose Nipple (Lintas)

### Features

- Superior Quality Investment-casted Stainless Steel.
- Available in S.S 304(CF8) & S.S 316(CF8M) Grades.
- Precise machining
- Available in BSP / BSPT / NPT Threading as per requirement.
- Pressure Rating PN25, Test Pressure(Hyd.): -30Kg./cm<sup>2</sup> (427 psig)
- Working Pressure 25 Kg./cm<sup>2</sup> (356 psig)

### Suitability

Water, Air, Gas, Oil, Steam



### Dimensions

Size	L (mm)	L (Inch)	S (mm)	S (Inch)	A (mm)	A (Inch)	B (mm)	B (Inch)
1/4"	48.00	1.89	17.20	0.68	5.00	0.19	8.60	0.33
3/8"	54.30	2.14	20.10	0.79	6.00	0.24	10.90	0.43
1/2"	56.70	2.23	24.20	0.95	9.00	0.35	14.50	0.57
3/4"	67.80	2.67	29.00	1.14	15.00	0.59	20.30	0.80
1"	76.50	3.01	35.90	1.41	18.00	0.71	25.50	1.00
1.1/4"	98.20	3.87	45.80	1.80	26.90	1.06	34.40	1.35
1.1/2"	104.00	4.09	52.00	2.05	33.20	1.31	39.90	1.57
2"	114.60	4.51	62.30	2.45	45.00	1.77	52.50	2.07
2.1/2"	136.3	5.37	80	3.15	55	2.17	64	2.52
3"	148	5.83	96	3.78	68	2.68	78	3.07
4"	157	6.18	119.9	4.72	90	3.54	103	4.06

