

## LI-EUN-01 Elbow Union F/F (Lintas)

### Features

- Superior Quality Investment-casted Stainless Steel.
- Available in S.S 304(CF8) & S.S 316(CF8M) Grades.
- Precise machining
- Available in BSP / BSPT / NPT Threading as per requirement.
- Pressure Rating PN25, Test Pressure(Hyd.): -30Kg./cm<sup>2</sup> (427 psig)
- Working Pressure 25 Kg./cm<sup>2</sup> (356 psig)

### Suitability

Water, Air, Gas, Oil, Steam



### Dimensions

| Size   | A (mm) | A (Inch) | B (mm) | B (Inch) | C (mm) | C (Inch) | D (mm) | D (Inch) |
|--------|--------|----------|--------|----------|--------|----------|--------|----------|
| 1/4"   | -      | -        | -      | -        | -      | -        | -      | -        |
| 3/8"   | 22.10  | 0.87     | 50.90  | 2.00     | 22.80  | 0.89     | 36.30  | 1.44     |
| 1/2"   | 27.70  | 1.09     | 58.70  | 2.31     | 27.30  | 1.07     | 41.00  | 1.61     |
| 3/4"   | 31.70  | 1.25     | 62.70  | 2.46     | 32.30  | 1.27     | 49.50  | 1.95     |
| 1"     | 36.40  | 1.43     | 70.30  | 2.77     | 40.60  | 1.61     | 58.00  | 2.28     |
| 1.1/4" | 43.80  | 1.72     | 77.00  | 3.03     | 49.30  | 1.94     | 68.30  | 2.69     |

