

LI-BV-01-3SE Stainless Steel 3 Pcs Ball Valve Screwed-End (Lintas)

Features

- Superior Quality Stainless-Steel Investment Casting
- Confirms to Class-150
- Design Standard BS EN ISO 17292 (BS 5351).
- Screwed Female Ends to BSPT / NPT.
- Three Piece Design.
- Superb in Quality and Performance.
- Available in SS304(CF8) & SS316(CF8M) Grades.

Test Pressure (Hydrostatic) :

Shell : 31 kg/cm²g (440 Psi)

Maximum Working Pressure: 21 kg/cm²g (300 psi)

Seat (Pneumatic) : 7kg/cm²g (100 psi)

Maximum Working Temperature: 220°C



Suitability

Water, Air, Gas, Oil, Steam

Materials of Construction

Part Name	Specifications / Material	Qty
Body	SS:304	1
Connector	SS:304	2
Ball	SS:304	1
Seat Ring	PTFE	2
Stem	SS:304	1
Ring Washer	PTFE	2
Gland Packing	PTFE	1
Thrust Bearing	PTFE	1
Stud / Nut	SS:304	4 Set
Spring Washer	SS:304	8
Gland Nut	SS:304	1
Stem Nut	SS:304	1
Lever	SS:304	1
Stem Washer	SS:304	1

Dimensions

Size (mm)	A	B	C
15	1/2" BSP/NPT	69.00	56.00
20	3/4" BSP/NPT	73.00	64.00
25	1" BSP/NPT	89.00	75.00
32	1.1/4" BSP/NPT	105.00	82.00
40	1.1/2" BSP/NPT	115.00	88.00
50	2" BSP/NPT	127.00	93.00

