

AQ-NRV-01 Stainless-Steel Multi Utility Check Valve (Screwed Ends) (AICQ)

Features

- Screwed Female Ends, available in BSP, NPT Threading standards
- Investment Casted Stainless-Steel, Available in CF8 & CF8M Grades
- Screwed in Bonnet.
- Spring Loaded closing Suitable for both Horizontal and Vertical Lines.
- Permits flow in one direction and shuts automatically if the flow reverses.
- The disc is guided in Body as well as in Bonnet.
- Tight shut-off lapped disc.



TEST PRESSURE

- Body: 300 Psig (Hydro.)
- Seat: 200 Psig (Hydro.)

Suitability

Water, Oil

Materials of Construction

Part Name / Number	Specifications / Material	Qty
Body (1)	CF8 / CF8M	1
Bonnet (2)	CF8 / CF8M	1
Disc (3)	CF8 / CF8M	1
Spring (4)	CF8 / CF8M	1
O- Ring	PTFE	1

Dimensions

Size (DN) mm	L mm	A
15	60.00	1/2" BSP/NPT
20	67.00	3/4" BSP/NPT
25	79.00	1" BSP/NPT
32	85.00	1.1/4" BSP/NPT
40	95.00	1.1/2" BSP/NPT
50	110.00	2" BSP/NPT

